

Preset Vandal proof Dome Camera

(Wall and Ceiling Mount)



Feature:

- I Die-Cast aluminum construction, vandal-proof
- I 0~12° both in pan and tilt, economic type
- I Strong wall mount, temper-proof wrench provided
- I 360° continuous pan, 90° tilt, shuttle scan, 32 presets totally
- I Armored housing, IP66 protecting grade
- I RS485 communication, multi-protocol, 24VAC

Specification

Model	SE604	SE604C	SE604C-A
Image Sensor		1/3' CCD	
Active Pixels		512 (H) x 582 (V)	795 (H) x 596 (V)
Synchronization		Internal	
Video Out		VBS 1.0Vp-p/75 Ohms	
White Balance		Auto	
Scanning frequency		15.625KHz (H) 50Hz (V)	
Horizontal resolution		420TVL	
S/N Ratio		≥ 48dB	
Electric Shutter		1/50~1/10,000 S	1/50~1/10,000 S
Min. Illumination		0.5Lux	
BLC		, On/Off	
Focal Length		4, 6, 8mm MTV lens	Auto iris lens 4~9mm
Gain		Auto/Manual (-3 to 28 dB, 2dB steps)	
Pan preset speed		12°/S	
Tilt preset speed		12°/S	
Pan speed		0~12°/S	
Tilt speed		0~12°/S	
Pan range		360°continously	
Tilt range		90°	
Preset &. Track		32 presets	
Communication		RS485 (multi-protocol, baud rate supported)	
Relative humidity		90% without agglomeration	
Work environment		Outdoor wall mount	
Work temperature		-10°C ~ +50°C	
Power supply		24VAC, 1.5A	
Power consumption		12VA	
Gross Weight		1Kg	